



# LED High-intensity Type A L856 Aviation Obstruction Light **AH-HI-A2**

This LED High-intensity Type A Aviation Obstruction Light flashing white color 24 hours and designed for marking top of obstacle that exceed 150 meters in height. Ultra high intensity CREE LED is used for the light source ensure light's long life experience and good performance. Self-designed reflection board ensure less LED could emitting brighter light.

### Compliance


- ICAO Annex 14 Volume 1, Sixth edition, 2013, table 6.3 High Intensity Type A Obstruction Light
- FAA L-856

### Features

#### Electrical

- CREE ultra high intensity LED as light source saving power
- Power supply available in DC(48V) or AC(110V-240V)

#### Physical

- Unique design and UV protected polycarbonate lens for converging light and saving LED power
- UV protection Powder coated bright yellow color base make better visibility
- Base material is powder coated die-casting aluminum which has strong corrosion resistance, Shock and Vibrations protection
-  Special valve installed beside the base to make sure the air could go through but water is avoid, so that the whole light temperature won't be high to destroy the light

#### System design

- Built-in photocell for day/twilight/night operation
- Surge and lightning protection

#### Optional

- Alarm contact for remote monitoring
- Infrared LED for pilot using NVG
- User adjustable flashing rate(40, 50, 60 flashes/minute)
- GPS synchronization

### Application

- AH-HI-A2 High-intensity light is used on the top of the High-rise Building, High Chimney, marking towers (Telecom, GSM, Microwave & TV), High Pole, Tower Crane, Wind Turbine, etc when the obstacle height is more than 150meter, and most time work with low intensity lights & medium intensity light installed on the lower place.



### APPLICATION



# LED High-intensity Type A L856 Aviation Obstruction Light AH-HI-A2

## Dimension(mm)



## Installation



(Mounting bracket is charged separately,  
and size is customized)

### SPECIFICATIONS

### AH-HI-A2 LED High-intensity Type A L856 Aviation Obstruction Light

#### Light Characteristics

Light Source	CREE high intensity LED
Available Colors	White
Intensity(cd)	≥200,000cd(Daytime) ≥20,000c((Twilight) ≥2,000cd(Night)
Horizontal Output(degrees)	360
Vertical Divergence(degrees)	4
Flash Characteristics	40-60 flashes per minute
Operation Mode	24hours operation, 3 different modes
LED Life Experience(hours)	>100,000

#### Electrical Characteristics

Operating Voltage	DC(48V, 24V, etc), AC(110-240V)
Average Power(W)	80W(40FPM)
Circuit Protection	Integrated

#### Physical Characteristics

Body Material	Polycarbonate
Base Material	Powder coated die-casting aluminum
Mounting	Ø190×Ø12
Dimension(mm)	236×236×545
Weight(kg)	7.5
Product Life Expectancy	10 years Plus

#### Environmental Factors

Humidity	0%-100%
Wind Speed	80m/s
Waterproof	IP67

#### Compliance

ICAO	Annex 14 Volume 1,'Aerodrome Design and Operations' Sixth edition 2016, table 6.3 High-intensity Type A White Obstacle Light L-856
FAA	L-856

#### Options Available

NVG(Night Vision Goggles) compatible LED
GPS Sync Flashing
Dry Contact alarm(NO COM NC)
User adjustable flashing rate (40, 50, 60)